FIELDHOLD · SATELLITE

FIELDHOLD ONE · Satellite

A complete satellite network in one sealed case. Set it down, connect power or the optional battery, press one button. The Starlink Mini works through the closed lid, with the Starlink router integrated in the panel. No separate router, no mast, no assembly.



~2 min*	128	IP56*	One
STARLINK ACQUISITION	DEVICES ON WI-FI	DESIGN TARGET	BUTTON TO GO

BUILT FOR

01 **Incident command and mutual aid**
A network at the post when towers are down or saturated, brought up by whoever arrived first.

02 **Remote and greenfield jobsites**
Broadband on site the day the trailer lands, without a carrier install or a service address.

03 **Live production and broadcast**
A path that does not collapse when the crowd arrives and saturates the venue network.

04 **Energy, mining and remote industrial**
SCADA, telemetry and safety systems stay reachable without a truck roll to a dead site.

UPGRADES

- Dual 99Wh battery pack, hot-swap and TSA carry-on compliant
- IP68 enclosure upgrade
- Starlink installation service, fitting a customer-supplied Mini

ORDERING

Priced by quote. Configure at **fieldhold.com/configure**, then request a quote from the summary. A person reviews shipping, tax and terms and replies within 24 hours.

No Starlink terminal is included.

Supply your own Starlink Mini, or we fit it as a service.

SPECIFICATIONS

CONNECTIVITY	
SATELLITE TERMINAL	Starlink Mini, works through the closed lid. Not included; customer-supplied or fitted by us as a service.
CELLULAR	Not equipped. See FIELDHOLD TWO.
WI-FI	Starlink router integrated into the panel. Wi-Fi 5 (802.11ac), up to 128 devices, coverage up to 112 m² (1,200 ft²).
ROUTER	None separate. The Starlink router is integrated; no second router.
POWER	
BATTERY	Optional dual 99Wh LiPo, hot-swap, TSA carry-on compliant. Charges from AC.
CHARGING & POWER	120VAC and 12VDC vehicle power, included.
RUNTIME	Pending manufacturer test data for the optional battery. *
PHYSICAL & ENVIRONMENTAL	
DIMENSIONS	18 × 13 × 6.9 in (457 × 330 × 175 mm) *
WEIGHT	15 lb typical, varies with options *
ENCLOSURE	High-impact resin
INGRESS PROTECTION	IP56 design target, IP68 optional
OPERATION	
CONTROLS	One button. Press and go.
DEPLOYMENT	Set the case, connect 120VAC, 12VDC or the optional battery, press the button. Lid stays closed.

FIELDHOLD is a brand of Ceasoned Inc.
310 Busse Hwy #370, Park Ridge, IL 60068 · support@fieldhold.com · https://fieldhold.com
Manufactured by Hertzian Labs LLC, Gilberts, Illinois.

Assembled in the USA from US and imported components. Not a life-safety device.
Starlink and cellular service are third-party services requiring separate accounts.
* Provisional values pending manufacturer confirmation.